

# FuRe Industrial (Shanghai) CO., LTD.

379#, Xin Sheng Road, Shanghai 201712  
Tel: +86-21-33884598 Fax: +86-21-59211909



## Datasheet

Issued Apr, 2014

# 锐腾 ReTeng<sup>®</sup> FS-60

### ● Description

Application            O-ring and gasket  
Form and Color        Sheet  
                                  White

### ● Reference Recipes and Properties

		R1
FS-60		100
101XL-45PS		1
TOTAL		101
Compression Moulding, 10 minutes at 175°C		
Post-Curing, 4 hours at 200°C		
Tensile Properties, T2 at 23°C		
Tensile Strength	MPa	10
Elongation at break	%	290
Hardness , 1 second at 23°C	Shore A	62
Tear Angle at 23°C	kN/m	15
Compression set, 22 hours at 180°C	%	6
Heat resistance, 70 hours at 200°C		
Tensile Strength Change	%	-14
Elongation Change	%	-6
Hardness Change	Points increase	3

- **Test Procedures**

Property Measured	Test Procedure
Tensile Properties	ASTM D412
Hardness Shore A	ASTM D1414
Compression set	ASTM D395

The information set forth herein is furnished free of charge and is based on technical data that FuRe Industrial believes to be reliable. It is intended for use by persons having technical skill, at their own discretion and risk. Since conditions of product use and disposal are outside of our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

锐腾 ReTeng® is a trademark of FuRe Industrial.

Copyright © 2014 FuRe Industrial. All Rights Reserved.